

County EVO part list

| 8301.081 | County EVO 230V/50-60Hz | | |
|----------|--|----------|--|
| 8301.082 | County EVO 230V/50-60Hz | 8301,131 | |
| | with accumulator, barcode input, printer output, watch | 8301.133 | |
| 8301.083 | County EVO 115V/50-60Hz | | |
| 8301.084 | County EVO 115V/50-60Hz | | |
| | with accumulator, barcode input, printer output, watch | 8301.141 | |
| 8301.050 | ISO9000 Traceable® Certificate | 8301.143 | |
| P | Accessories for the counting of PTH taped components | | |
| 8301.023 | Complete support for rolled bandolier(1 pcs) | 8301.350 | |
| 8301.025 | | | |
| | | 8301.150 | |
| | Accessories for the counting of SMD components | | |
| 8301.018 | SMD Adaptor | 8301.110 | |
| 8301.028 | SMD support for rolled bandolier | | |

County-S EVO part list

| 210 pa/1//01 |
|---|
| County-S EVO 230V/50-60Hz County-S EVO 230V/50-60Hz with Empty Pocket Check |
| County-S EVO 115V/50-60Hz County-S EVO 115V/50-60Hz with Empty Pocket Check |
| ISO9000 Traceable® Certificate |
| upport for reels > 400mm diameter |

Empty Reel, aluminium made, 350mm diameter

Barcode for County EVO and County-S EVO

It's small, lightweight and ergonomic design, coiled cable included, a wider than usual scan angle provides the ability to read a longer bar code from a shorter distance, IP42 protection.

The barcode is connected and powered via a single cable, without the hassle of two separate cables.

8301.155

8301.030

Barcode with coiled cord

SMD bandolier handle



Printer for County EVO and County-S EVO

Direct thermal label printer built for ease-of-use and durability, ac adaptor 110-230Vac and data cable included.

Maximum print width is 104mm however the print is optimized for 57x51mm labels



8301.095 8301.096 Direct thermal label printer 57x51mm, 1360 labels/roll

COUNTER-PEN™

Counter-Pen $^{\text{TM}}$ is a combination marker and digital counter designed for the lab and plant.

Each time a black mark is made with the felt-tipped pen, it automatically sounds a beep, and LCD displays the counts. It is very useful to count components, packages and during inventory

Durable ABS plastic unit provides audio/visual counts to 99999 with reset button, on/off switch, and pen cap.

8301.120 8301.122

BY WEIDNER

COUNTER-PEN digital counter Replacement pen cartridge



Test Weights

All counting scales can be calibrated using the internal software, and a certified test weight. To achieve optimum accuracy from the balance, it should be adjusted in the locality where it is used, because the latitude and longitude affect the calibration and the strain gauge cell could go out of adjustment during the transportation.

| 8301.296 | Test Weight 0.02Kg | F1 class - case - DKD certificate |
|----------|--------------------|-----------------------------------|
| 8301.300 | Test Weight 0.1Kg | F1 class - case - DKD certificate |
| 8301.303 | Test Weight 0.5Kg | F1 class - case - DKD certificate |
| 8301.305 | Test Weight 1Kg | F1 class - case - DKD certificate |
| 8301.310 | Test Weight 2Kg | F1 class - case - DKD certificate |
| 8301.315 | Test Weight 10Kg | F1 class - case - DKD certificate |

